


# AGRICULTURE



## PENBLITZ 228M

Heavy Duty Alkaline Cleaner

### FEATURES/BENEFITS

- Free of caustic, phosphates, & solvents
- High foaming
- Odorless
- No VOCs
- Suitable for use in high pressure & automatic foaming systems
- Effective on wide variety of soils
- Compatible with most materials

Penblitz 228M is available in 55 gallon drums and 5 gallon pails. Inquire about availability in other packages.

1882.bulus-ag.wpd

(May07)

### Description

*Penblitz 228M* is a caustic free high foaming liquid alkaline cleaner designed for use in heavy duty automatic foaming systems.

### Typical Use Directions (also see product label)

**Equipment to be treated** Industrial equipment, floors, walls, mobile machinery, cars, trucks, trailers

**Soils to be removed** Lubricants, rubber marks, animal fat, ink, adhesives, wax, motor exhaust deposits

**Use procedure** Apply using a mop, trigger or automatic sprayer or automatic foaming system

**Concentration** Between 2% and 10% (3-12 oz/gal)

**Use Temperature** By immersion: a minimum of 120°F  
As foam: between 50° and 160°F

**Dwell time / Operation time** Allow to dwell 3 to 5 minutes before final rinsing

**Mechanical action** Scrubbing, high pressure application and rinsing recommended to remove stubborn deposits

**Rinsing** High pressure hot water

**Reuse / Recycling** No

SEE REVERSE SIDE

**IMPORTANT:** Before using *PENBLITZ 228M*, always be sure to read and follow warnings and directions for use appearing on the product container label and MSDS.

Penetone Corporation • 700 Gotham Parkway • Carlstadt, NJ 07072 • (800) 631-1652  
West Penetone, Inc. • 10900 Secant St. • Ville d'Anjou, QC H1J 1S5 • (514) 355-4660



YOUR CLEANING SOLUTIONS RESOURCE.

# PENBLITZ 228M

## Heavy Duty Alkaline Cleaner

### PHYSICAL PROPERTIES, typical

<b>Appearance:</b>	Clear colorless liquid	<b>Flash Point, TCC, °F:</b>	None
<b>Odor:</b>	Detergent	<b>Viscosity:</b>	Thin
<b>Specific Gravity @ 20°C:</b>	1.09	<b>Foaming:</b>	Very high
<b>pH at 1%:</b>	13	<b>Concentration Monitoring Technique:</b>	Titration, conductivity, refractive index
<b>Boiling Point, °F:</b>	Approx. 212	<b>Rinsability:</b>	Excellent
<b>Freezing Point, °F:</b>	<32		
<b>Contains:</b>	no phosphates		

### INCOMPATIBILITY

Alkaline and chlorinated products, reducing agents

### WAREHOUSING PRECAUTIONS

Keep from freezing

**IMPORTANT:** Before using PENBLITZ 228M, always be sure to read and follow warnings and directions for use appearing on the product container label and MSDS.

Penetone Corporation • 700 Gotham Parkway • Carlstadt, NJ 07072 • (800) 631-1652  
West Penetone, Inc. • 10900 Secant St. • Ville d'Anjou, QC H1J 1S5 • (514) 355-4660



YOUR CLEANING SOLUTIONS RESOURCE.