

## GENERAL PRODUCT



# WESTOP™ 450

## Water Based Corrosion Inhibitor

### FEATURES/BENEFITS

Concentrated  
Water Soluble  
Soluble in Alkaline Cleaners  
Odorless  
Apply in Rinse Water or Dip Tanks  
Economical  
Easy to Use  
Nonirritating Solution  
No Removal Needed Prior to Printing, Plating, or Assembly

Westop 450 is available in 55 gallon drums and 6 gallon pails. Inquire about availability in other packages.

3295a.bul.wpd (Apr06)

### Description

*Westop 450* is a water based corrosion inhibitor that coats metals with a dry microscopic film, thereby ensuring protection against corrosion, acid fumes, and moisture for a period of up to six months.

#### ***Westop 450* can be used:**

- when cleaning, washing or tumbling ferrous metal parts prior to enameling or plating.
- in hydrostatic pressure-testing of ferrous castings, valves, pumps, compressors, etc. .
- in heat treating operations in the final rinse cycle after salt removal.
- as a corrosion inhibitor in the final rinse cycle during spray wash cleaning.

### Typical Use Directions (also see product label)

**Spray Washers** - Use a concentration of 2 to 4 oz. per gallon of water at operating temperatures of 68°-150° F. Optimum temperatures are 130°-140° F.

**Dip Tanks** - Use at a concentration of 2-5%, at 68° - 140° F.

***Westop 450*, as supplied, is incompatible with acids.**

**IMPORTANT:** Before using *Westop 450*, always be sure to read and follow warnings and directions for use appearing on the product container label and MSDS.

Penetone Corporation • 700 Gotham Parkway • Carlstadt, NJ 07072 • (800) 631-1652  
West Penetone, Inc. • 10900 Secant St. • Ville d'Anjou, QC H1J 1S5 • (514) 355-4660



YOUR CLEANING SOLUTIONS RESOURCE.