

GENERAL PRODUCT



PENSOLV™ C64

Solvent Paint, Gun Metal Cleaner, Degreaser

FEATURES/BENEFITS

Features

- Fast evaporation
- Free of MEK, Toluene, MIBK
- Non-ozone depleting
- Dries with no residue
- 170°F TCC flash point
- Safe on all metals

Benefits

- Not flammable
- No red label storage
- Less fire hazard
- Safer to use

Pensolv C64 is available in 6 gallon pails or 55 gallon drums

Description

Pensolv C64 is a unique approach to minimize the fire hazards encountered when using highly flammable solvents to clean painting equipment or remove adhesive deposits.

Pensolv C64 does not require flammable solvent storage and is also an excellent general cleaning solvent recommended for textile mills, printing plants and electrical repairs. *Pensolv C64* should be used where very rapid drying and no residue are required.

Directions for Use

Pensolv C64 is to be used full strength. Do not dilute with water. Do not heat.

To Clean Paint Gun:

Inject *Pensolv C64* undiluted through paint gun nozzle for one to four seconds to remove paint build-up.

Regular Cleaning:

Apply undiluted using low pressure, non-atomizing coarse spray. Allow solvent to penetrate soils; follow by blowing dry with compressed air. Other methods of application include wiping, brushing or tank immersion. Where a tank immersion process is recommended, tanks should be covered when not in use.

Note:

Safe for use on all metals. May craze or soften certain plastics or paints. Pretest on plastic or painted surfaces before using.

IMPORTANT: Before using *PENSOLV C64*, always be sure to read and follow precautions and directions for use appearing on the product container label and MSDS. (Sep06)